700x500 mm

600x600 mm

Profile

Wallmount

60 mm

Power supply
12x3x2 cm

Installation screws x 4 units

40 mm

10 mm

200 mm   260 mm

260,00 mm   200 mm

500 mm

600 mm

6 mm

80 mm

80 mm

Hole
diameter
10 mm

60 mm

70 mm

12,00 mm

Connections access

60 mm

40 mm   60 mm   70 mm

600 mm

80 mm

700 mm

Power supply
12x3x2 cm

682 mm

782 mm

Illuminated round corners projecting sign.

COLOURS

- **Aluminium Profile:** White satin (RAL 9010)
- **Wallmount:** Light gray satin (Pantone Cool Gray 2)
- **Acrylic:** Opal white.

Opal acrylic 3mm

LED:
Lumens per meter: 27 lm/m.
Power comsumption per meter: 6 W/m.
Chip type: 2825

Powder coated
aluminium profile

Access cover
power supply

Connection
cable

LED guided light
panel: 5 mm

Opal acrylic 3mm

A
A

Section A-A

Profile
section

Profile union

Acrylic

Guided light
panel 5 mm.

Illuminated round corners projecting sign

COLOURS

- **Aluminium Profile:** White satin (RAL 9010)
- **Wallmount:** Light gray satin (Pantone Cool Gray 2)
- **Acrylic:** Opal white.